

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: 6 HES 749, Section 17 T. 34N. R. 34W. P.M.M. Lincoln County

1917 GLO Record: Set a small stone, marked with a cross (x) under a quartzite stone, 26 ins. x 8 ins. x 5 ins., 16 ins. in the ground, marked "6HES749" on West face and a cross (x) on top for exact corner point, from which:

- A Black pine, 10 ins. dia., bears N4°E, 47 lks (30.0 ft.), marked with a cross and scribed "6HES749BT"
- A White pine, 12 ins. dia., bears N77°15'W, 24 lks (15.8 ft.), marked with a cross and scribed "6HES749BT"

Raise a mound of earth, 4 ft. base, 2 ft. high, West of corner.

2010 Found: We find a stone monument, 5-1/2 ins. x 10-1/2 ins., 1.1 ft. above ground, marked "6HES749" on the West face. No evidence of bearing trees found.

2010 Perpetuation: Establish new bearing trees as follows:

- A Cedar, 11 ins. dia., bears N51°E, 13.8 ft., scribed "6HES749RM2"
- A Cedar, 9 ins. dia., bears S67°E, 4.0 ft., scribed "6HES749RM1"

Bearing trees affixed with BT tags, LSM signs, snow blazed and painted red bands.

Steel spikes driven into BT's, side center at point of measurement.

We set a galvanized steel post N47°W, 0.3 ft from monument, with LSM and USFS boundary decals.

See back side for corner exhibit

<p style="text-align: center;">Found Stone</p> <p style="text-align: center; margin-top: 100px;">SKETCH OF CORNER</p>	<p style="text-align: center;">CERTIFICATION</p> <p>I, <u>Keith Brandt</u> certify the information shown herein is true and correct.</p> <p style="text-align: center;"><i>Keith Brandt</i> Signature Ground Party Chief</p> <p>I, <u>Ken E Jenkins</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101).</p> <p style="text-align: center;"><i>Ken E Jenkins</i> Signature of Surveyor & Seal</p> <p>Date: <u>1/2011</u> Reg. No. <u>9330 LS</u> Employer: <u>Montana Northwest Company</u> <u>P.O. Box 8777, Missoula, MT 59807</u> <u>406-721-4033 Project No. 1617-10</u></p>
--	--

Office of Clerk and Recorder, County of _____

record" was filed for record

was noted on the cross-index


book No. _____

This "corner
PAGE: 11865 Pages: 2

231922 BOOK: CCR CC&R'S
STATE OF MONTANA LINCOLN COUNTY
RECORDED: 03/31/2011 10:40 KOI: CC&R'S
TAMMY D. LAUER CLERK AND RECORDER
FEE: \$0.00 BY: *Debbie Stearns*
TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official

Sec. 17



Cross Index No. 6HES 749 T. 34N R. 34W PMM

● - Corner this sheet

- Corner this sheet

STATE LINE
MONUMENT
NO. 28

N.F.S.L.

2 & CC

UNSURVEYED SEC. 8

IDAHO
MONTANA

N.F.S.L.

HES 750
PRIVATE

UNSURVEYED SEC. 17

STATE LINE
MONUMENT
NO. 29 & COR.
1 HES 750

STATE LINE

HES 113
PRIVATE

HES 749
PRIVATE

N.F.S.L.

2 & CC

N.F.S.L.

N.F.S.L.

STATE LINE
MONUMENT
NO. 30

UNSURVEYED SEC. 20

