

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: 4 HES 113, Section 17 T. 34N. R. 34W. P.M.M. Lincoln County

1913 GLO Record: Set a slate, quartzite stone, 24 ins. x 17 ins. x 6 ins., 14 ins. in the ground for Cor. No. 4, with a cross (x) cut in top at the exact cor. point and "4HES113" cut in Southwest face from which:

A Tamarack, 20 ins. dia., bears S62°35'W, 2.23 chs. (147.18 ft.), blazed and scribed "3HES113BT"
No other trees available

Dug a pit, 24 ins. x 24 ins. x 12 ins. deep at S45°E, 7 ft., and a pit 24 ins. x 24 ins. x 12 ins. deep at S64°W, 7 ft. Raised a mound of earth, 4 ft. base and 2 ft. high Southwest of corner.

2010 Found: We find a stone monument, 5-1/2 ins. x 12 ins., 0.5 ft. above ground, marked "4HES113" on the Southeast face from which:

A Larch stump, 20 ins. dia., bears S64°W, 148.8 ft., with no visible evidence.

2010 Perpetuation: Establish new bearing trees as follows:

A Grand fir, 12 ins. dia., bears S15°W, 9.0 ft., scribed "4HES113RM1"
A Grand fir, 15 ins. dia., bears N17°W, 8.1 ft., scribed "4HES113RM2"
Bearing trees affixed with BT tags, LSM signs, snow blazed and painted red bands.
Steel spikes driven into BT's, side center at point of measurement.
We set a galvanized steel post East, 0.6 ft from monument, with LSM and USFS boundary decals.


See back side for corner exhibit

Found Stone	CERTIFICATION I, <u>Keith Brandt</u> certify the information shown herein is true and correct. <u>Keith Brandt</u> Signature Ground Party Chief
	I, <u>Ken E Jenkins</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq.) <u>Ken E Jenkins</u> Signature of Surveyor & Seal Date: <u>1/2011</u> Reg. No. <u>9330 LS</u> Employer: <u>Montana Northwest Company</u> <u>P.O. Box 8777, Missoula, MT 59807</u> <u>406-721-4033 Project No. 1617-10</u>
SKETCH OF CORNER	

Sec. 17

Office of Clerk and Recorder, County of _____ This "corner record" was filed for record on: 231923 BOOK: CCR CCLER'S PAGE: 11866 Pages: 2
was noted on the cross-index: STATE OF MONTANA LINCOLN COUNTY
book No. _____ RECORDED: 03/31/2011 10:42 KOI: CCLER'S
TAMMY D. LAUER CLERK AND RECORDER
FEE: \$0.00 BY: Joanne Lewis Deputy
TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official



- Corner this sheet

STATE LINE
MONUMENT
NO. 28

N.F.S.L.

2 & CC

IDAHO
MONTANA

UNSURVEYED SEC. 8

N.F.S.L.

HES 750
PRIVATE

UNSURVEYED SEC. 17

STATE LINE
MONUMENT
NO. 29 & COR.
1 HES 750

STATE LINE

HES 713
PRIVATE

HES 749
PRIVATE

N.F.S.L.

2 & CC

N.F.S.L.

N.F.S.L.

STATE LINE
MONUMENT
NO. 30

UNSURVEYED SEC. 20

