

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

COR. 3 of HES 407
 Corner _____ T. 34 N. R. 33 W. P.M.M. Lincoln County

- I. 1915 H.E.S. original record by Elmer R. Johnson: Set for Cor. No. 3, a sandstone, 28x15x8 ins., 18 ins. in the ground, marked 3 HES 407 on SW face, and a cross (x) on top for the exact corner point, from which:

A cross (x) on a larch, 7 ins. diam., bears $S10^{\circ}20'E$, 44 lks. dist.
 A cross (x) on a larch, 8 ins. diam., bears $N85^{\circ}48'W$, 10 lks. dist.
 Each blazed and scribed 3 HES 407 BT.

Raise a mound of stone, 4 ft. base, 2 ft. high, West of corner.

- II. Found a 15x8 in. sandstone, firmly set, protruding 8 ins. above the ground, mkd. 3 HES 407 on SW face, from which:


No evidence of the original bearing trees, except a stump hole and mound bears $N85^{\circ}W$, 6.6 ft. dist.

- III. I established two new bearing tree

A larch, 12 ins. diam., bears $N6^{\circ}E$, 20.6 ft. dist., mkd. 3 HES 407 BT.
 A larch, 12 ins. diam., bears $S80^{\circ}E$, 26.3 ft. dist., mkd. 3 HES 407 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, $S59^{\circ}E$, 3 ft.
 Magnetic declination: 20° East.



SKETCH OF CORNER

CERTIFICATION

I, Tom Hommel

certify the information shown herein is true and correct.

Tom Hommel
 Signature Ground Party Chief

I, Alvah F. Hughes

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Alvah F. Hughes
 Signature of Surveyor & Seal

Date: 11/16/91 Reg. No. 7322


Employer: U.S. FOREST SERVICE

ALVAH F. HUGHES
 7322 LG
 REGISTERED

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on 4-21-92 was noted on the cross-index plat and is assigned page No. 5042, in book No. _____

County Official Coral M. Cunningham

3 HES 407 34 N 33 W
 Cross Index No. _____ T. _____ R. _____ P.M.M.



• - corner this sheet