(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the 1/4 corner common to Sections $\frac{7}{18}$, T35N, R27W, Lincoln County, Montana,

FOUND: Original tree to be cut, but stump in good condition, with a 5/8" rebar drove in the top. New RM's had been set by the BLM.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: July 15, 1980

At the corner a witness corner was set. A 3/4" aluminum cap on a $2-\frac{1}{2}$ " x 30" pipe, 26" in the ground. Witness corner bears N.5½°E., at 8.6 feet from original corner. Used two bearing trees for the original corner to reference the witness corner.

A 16" fir bears S.3°W., 35.8 feet A 12" fir bears S.83 $\frac{1}{2}$ °E., 45.4 feet

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See	Certificate	of	Survey	No.	•

Surveyor's Seal



Paul S. Long, Jr.

certify that the information shown herein is true and correct.

Gaul J. Jong.
Signature of Ground Party Chief

R. David Schurian


certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> rca Signature of Surveyor

> > 3102S

Registration Number

DIAGRAM OF CORNER:



Lincoln Office of Clerk and Recorder, County of

This "corner record" was filed for record on the 25...... day of

35N

assigned page No. 20, in book No.

Cross Index No.