

CERTIFIED LAND CORNER RECORDATION

SECTION 7 TWP. 35 N., R. 27 W., P.M.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Corner evidence reported on OTHER SIDE

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Office

Date of work: April, 1980

CORNERS SET _ this survey - indicated and described on
DIAGRAM ON REVERSE SIDE

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE DIAGRAM ON REVERSE SIDE

Surveyor's Seal

I, Jack H. Ninneman 4661 S.
certify that the information shown herein is true and
correct.

Jack H. Ninneman
Signature of Ground Party Chief

I, J.H. Ninneman
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

Jack H. Ninneman
Signature of Surveyor

DIAGRAM OF CORNER:

N.

SEE REVERSE SIDE

= Corner recorded on the sheet

4661 S.

Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 31st day of July 1980, was noted on the cross-index plat and is
assigned page No. 882, in book No. _____

Eleanor L. Vaughn by Sherry L. Hawks
County Official Deputy

T. 35 N., R. 27 W.

91

1 6
12 7

TWP. 35 N., R. 28 W., M.P.M.
TWP. 35 N., R. 27 W., M.P.M.

B.L.M.
B.C.

N 0° 07' 56" W
2631.04'

S 89° 51' 28" W
2625.13'

TWP. 35 N., R. 27 W.
M.P.M.
7

S 89° 51' 28" W
1321.78'

B.L.M.
B.C.

N 0° 07' 56" W
1316.78'

N 0° 07' 12" W
1317.47'

N 0° 06' 28" W
1318.16'

N 0° 05' W
1319.52'

S 89° 55' 02" W
1321.22'

N 0° 07' 56" W
658.39'

N 0° 06' 28" W
658.74'

S 89° 56' 48" W
1320.94'

N 0° 05' W
658.76'

12 7
13 18

Steel Rod
In Stump
Posted By B.L.M.
1 Orig. B.T.
Stump
2 New B.T.s

S 89° 58' 35" W
1320.66'

7 8
18 17

B.L.M.
B.C.

1. Set A 1/2" X 24" Steel Rod
With Cap Stamped
J.N. 534 E.S.

2. Set A 1/2" X 24" Steel Rod
With Cap Stamped
J.N. 534 E.S.

3. Set 1/2" X 24" Steel Rods
With Caps Stamped
J.N. 534 E.S.

4. Set a 5/8" x 24" Steel Rod
with Yellow Cap Stamped:
J.H.N. 4661 S.

4" Fir Bears N 25° W 8.30 Ft.
Posted

A Railroad Tie Post Bears N 13° W 22.60 Ft.
Posted

At Remaining Subdivision Corners Designated
(No B.T.s Scribed Or Posted)

6" Larch bears S 86° W 6.6 Ft. Scribed:
1/16 S 7 BT and Posted.
8" Fir bears S 11° E 6.9 Ft. Scribed:
S 1/16 S 8 BT and Posted.

18" Larch Stump bears West 4.0 Ft.
with Location Poster. No B.T.s

LLEWELLYN, STACEY, DIAS, SNAFFER, SCHENDEL (EUREKA)