CERTIFIED CORNER RECORDATION

Corner	Cor. 4 H.E.S. 457	Sec.	6	Т.	35N	R.	31W	P.M., MT	Lincoln	County

I. 1915 G. L. O. original notes by Fred E. Thieme: Set for Cor. No. 4, a small stone, marked with a cross "X" under a quartzite stone, 26 X 16 X 8 ins., 16 ins. in the ground, marked 4 HES 457 on NE. face, and a cross "X" on top for the exact corner point, from which:

A cross "X" on a lodgepole pine, 9 ins. diam., bears S 10°13' W, 22 lks. dist.

A cross "X" on a lodgepole pine, 7 ins. diam., bears S 63°00' W, 11 lks. dist., each blazed and scribed 4 HES 457 BT.

Raise a mound of earth and stone, 4 ft. base, 2 ft. high, NE. of corner.

II. Found a stone, 5 X 12 ins., 10 ins. above the ground, firmly set and mkd. 4 HES 457 on NE face, and a cross "X" on top, mound of earth and stone NE of the corner, from which:

A pine, 10 ins. diam., bears N 62°E, 13.1 ft. (19.8 lks.), mkd. with visible ax marks. A dead pine, 11 ins. diam., bears S 76°W, 6.0 ft. (9.1 lks.), mkd. 4 HES 457 BT.

III. Establish two new bearing trees:

A fir, 19 ins. diam., bears N 61°E, 34.6 ft. dist., mkd. 4 HES 457 BT. A fir, 8 ins. diam., bears N 60°W, 25.7 ft. dist., mkd. 4 HES 457 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East

S 76°W 60 m	CERTIFICATION Jeff Hintz certify the information shown herein is true and correct. Signature Ground Party Chief Alvah F. Hughes certify that this Corner Record correctly represents work performation, Act, (70:22-101, et.sp., M.C.A.) Signature of Surveyor Spall Date: 12/14/95 Reg. No.: 7322LS
SKETCH OF CORNER	Employer: U.S. FOREST SERVICE
Office of Clerk and Recorder, County of LINCOLN. This "coon JULY 29,1997 was noted on the cross-index plat and in book No.	

County Official

corner this sheet