CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

6 HES 274

Corner No. 6 was not found. Bearing trees were not found.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

8/20/64

Date of work:..

A quartzite 18" x 10" x 12" boulder was set 10" in the ground. An "X" was scribed on top for the exact point. No trees or buildings were available for reference. A rock mound, 4' diameter and 3' high, was constructed 3' east of the monument.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

½" iron pin 12" long was driven at each station.

520° 12'E 269.4" 1484.7 5.33°04' E.

Surveyor's Seal

I, George Murphy certify that the information shown herein is true and correct.

will W- Murd Signature of Ground Party Chief

E. R. Sievers

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

Rock Mound

= Corner recorded on the sheet

1946 E.S. Registration Number

Office of Clerk and Recorder, County of LINCOLN, LIBBY, MONT. This "corner record" was filed for record on the 22nd. day of September 1964, was noted on the cross-index plat and is M. M. MANSFIELD, By: Mac Watson Deputy. assigned page No. 21 in book No. 1