

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 4 of HES 1064 T. 35 N. R. 32 W. P.M.M. Lincoln County

- I. 1921 H.E.S. original record by Grant Higgins: Set a granite stone, 30x9x6 ins., 20 ins. in the ground, mkd. 4 HES 1064 on SW face and a cross (x) on top for exact corner position,

from which:

A cross (X) on a larch tree, 7 ins. diam., bears S. $36^{\circ} 41'$ W., 87 lks. dist.

A cross (X) on a larch tree, 6 ins. diam., bears N. $11^{\circ} 28'$ E., 135 lks. dist.

Each blazed and scribed 4 H E S 1064 BT.

Raise a mound of earth and stone 4 ft. base, 2 ft. high, SW. of Corner.

- II. Found a firmly set stone, 30x9x6 ins., marked 4 HES 1064 on the SW. face, and with a cross on top. No evidence of original bearing trees.

- III. Established two new bearing trees:

A larch, 14 ins. diam., bears S. 74° E., 37.6 ft. dist, scribed 4 HES 1064 BT.

A larch, 15 ins. diam., bears S. 21° E., 62.6 ft. dist, scribed 4 HES 1064 BT.


Cleared duff and earth from around stone.

Raise a mound of stone 3 ft. base diam. 12 ins high, SW. of corner.

Painted red bands around the bearing trees and attached "Land Survey Monument" and "Bearing Tree" signs where needed.

Set a 6 ft. galvanized steel guard post with "Land Survey Marker" and "Property Boundary" decals, S. 79° W., 4.0 ft. dist.

Magnetic declination: 20° East



SKETCH OF CORNER

CERTIFICATION

I, Kenneth Kern
certify the information shown herein is true and correct.
Kenneth R. Kern
Signature Ground Party Chief

I, Alvah F. Hughes
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.).
Alvah F. Hughes
Signature of Surveyor & Seal

Date: 11/26/91 Reg. No. 7322 LS 7322 LS
Employer: U.S. FOREST SERVICE


Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on 4-21-92 was noted on the cross-index plat and is assigned page No. 5034, in book No. Coral M. Cummings

County Official i

4 HES 1064

35 N 32 W

Cross Index No. T. R. PMM



• - corner this sheet