CERTIFIED CORNER RECORDA

T. <u>35</u> N., R. <u>32</u> W., P.M.M. <u>Lincoln</u> County Corner No. 1 HES 408

Record:

1915 HES 408 by F.B. Thieme

"Set a small stone, marked with a cross (x) under a sandstone 28x13x4 ins., 18 ins. in the ground, marked 1 HES 408 on E face, and a cross (x) on top for exact corner point, from which:

A cross (x) on a Lodgepole Pine tree, 9 ins. dia., bears N 63°20' W, 16 lks. dist. A cross (x) on a Lodgepole Pine tree, 10 ins. dia., bears N 11°53' E, 18 lks. dist., each blazed and scribed 1 HES 408 BT. Raise a mound of stone, 4 ft. base, 2 ft. high, E of corner."

Found Evidence:

A sandstone 11x3 ins., 12 ins. exposed above ground, marked 1 HES 408 on the E face with a cross (x) on top, from which:

A well rotted Lodgepole Pine bears N 59° W with a visible scribed face, no dist. was measured due to being able to determine the exact original position.

A mound of stone, 3 ft. base, 2 ft. high, bears NE of corner.

Perpetuation:

I accept the marked stone for Corner No. 1 HES 408.

We established two (2) new Bearing Trees described as follows:

County Official

Cross Index No. <u>1 HES 408</u> T. <u>35</u> N., R. <u>32</u> W., PMM

A Lodgepole Pine 17 ins. dia. bears N 17°30' W, 28.00 ft. dist., scribed "1 HES 408 BT". A Larch 19 ins. dia. bears N 68° W, 25.60 ft. dist., scribed "1 HES 408 BT".

Painted scribed faces red and 6 inch wide bands around both Bearing Trees.

Attached Land Survey Monument and Bearing Tree signs to both trees.

Set a steel post on line 3 ft. SE of corner with attached monument and property line stickers.

Office of Clerk and Recorder, County of JMColor. This "comer record" was filed for record on Jd 14, 1997 was noted on the cross-index plat and is assigned page No. 9	9.78 LIDES No. 408
0 . 1	Section
Sketch of Corner	Date: 10/13/9 Reg. No. 4975-S Employer:
19" LARCH 25.60 PINE DOR NO. 1 HES 408	Signature of Surveyor & Seal
OPO 17" LONGE	CERTIFICATION

THIS CORNER