CENTIFIED CORNER RECORD. ION

Corner No. 3 HES 408 T. 35 N., R. 32 W., P.M.M. Lincoln County

Record:

1915 HES 408 by F.B. Thieme

"Identical with Cor. No. 6 of unapproved HES No. 406, a shale stone 10x15x4 ins. above ground, as set by me on July 17, 1915. I mark this stone for Cor. No. 3, 3 HES 408 on SW face, from the cross on top:

A cross (x) on a Balsam tree, 13 ins. dia., bears S 30°10' E, 12 lks. dist. A cross (x) on a Balsam tree, 8 ins. dia., bears N 52°20' E, 21 lks. dist., each blazed and scribed 3 HES 408 BT.

Raise a mound of earth, 4 ft. base, 2 ft. high, SW of corner."

1989 Corner Recordation by A.F. Hughes USFS.

Found Evidence:

A shale stone 18x4 ins., 12 ins. exposed above ground, marked 3 HES 408 on the SW face with a cross (x) on top, from which:

A Spruce 7 ½ ins. dia., bears N 21° W, 35.60 ft. dist., with visible scribing. A Spruce 18 ins. dia., bears S 62° E, 15.10 ft. dist. This Bearing Tree has fallen over with scribed face down.

A steel guard post bears 3 ft. N of stone monument with Property Line and Land Survey Monument stickers.

Perpetuation:

I accept the stone monument for Cor. No. 3 HES.

We establish one new Bearing Tree described as follows:

A Spruce 17 1/4 ins. dia. bears S 40° E, 31.70 ft. dist., scribed "3 HES 408 BT".

Painted scribed faces red and 6 inch wide bands around the Bearing Trees and attached Land Survey Monument and Bearing Tree signs where needed.

Magnetic Declination: 19° East

3, 8.	Ser my direction id compliance with the "Corner Recoration Act
Sketch of Corner Employe	13/9 Reg. No. 4975-S

