
## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.



- corners.

  3. Description of monument and accessories set to perpetuate the corner position.

  4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

  5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana,

  6. Fill in Cross Index & Section Diagram at bottom of sheet.

1921 H.E.S. original record by Grant Higgins: Placed a small stone, marked with a cross (x) under a granite stone, 24x8x6 ins., 14 ins. in the ground, marked 3 HES 1071 on SW face and a cross (x) on top for

A cross (x) on an alder tree, 4 ins. dia., bears S39 09'W, 26 lks.(17.16 ft.) dist. A cross (x) on an alder tree, 4 ins. dia., bears N7 23'W, 18 lks.(11.88 ft.) dist.

Corner 3 of HES 1071

the exact corner point, from which,

## CERTIFIED CORNER RECORDATION.

T. 35 N., R. 33 W., P.M.M. Lincoln

| Each blaze         | ed and scribed 3 HES 1071 BT.  |  |
|--------------------|--|--|
| Raise a mound o    | of stone, 4 ft. base, 2 ft. high, SW of corner.  |  |
|                    | ns. stone, firmly set, protruding 9 ins. out of<br>. Mound of stone, 3 ft. dia., 1 ft. high, SW of   |  |
| No evidence of     | bearing trees found.   |  |
| A spruce,          | o new bearing trees<br>11 ins. dia., bears N24 <sup>°</sup> E, 29.7 ft. dist., mkd.<br>8 ins. dia., bears N83 <sup>°</sup> E, 17.9 ft. dist., mkd. 3 | 3 HES 1071 BT. HES 1071 BT.  |
| Set a 6 ft. ga     | nds around the bearing trees and attached Land S<br>lvanized steel guard post with Land Survey Marke<br>nation: 20 East.                             | urvey Monument and Bearing Tree signs.<br>r and Property Boundary decals, \$3 W, 3 ft.   |
|                    |  |  |
|                    |  |  |
|                    |  | ·  |
|                    |  |  |
|                    |  |  |
|                    |  |  |
|                    |  |  |
| -                  | I'' SPRUCE   | CERTIFICATION  |
| •                  | ₩.   | i, Gary Crismon certify the information shown herein is true and correct   |
| Λ                  | **/^.  | Josep Crismon  |
| 4                  | N83°E \$ 8"CEDAR   | Alvah F. Hughes ONT  |
|                    | N83E<br>17.9 FT.   | certify that this Corner Record correctly represents work performed  |
| h                  |  | by me or under my direction in compliance with the Cornei<br>Recordation Act" (70-22-101, et seq. M.C. A)  |
|                    |  | Signature of Street of Asian Form  |
| l                  |  | Date: 1/8/91 Reg. No. 2022 1585  |
|                    | SKETCH OF CORNER   | Employer: U.S. FOREST SERVICE  |
| Office of Clerk as | 1 . 1  | Sec. 17 in Se |
|                    | d for record on  |  |
|                    | cross-index plat and is assigned page No.  | 4470 , in #E5  |
| book No.           | Coral M Cummur   | so by But Buelon 3   |
|                    | County O   | fficial/   |
|                    | 3 HES 1071   | 35 N 33 W  |

\_ РММ

• - corner this sheet