	CERTIFIED CORNER RECORDATION
	CornerCN 1/16 S29 T35N R25W P.M.MLincolnCounty
	<u>Original GLO Notes:</u> This corner was never set.
	1982 Michael L. Haiges:
	Set: An Alum. Monument with Cap, 3¼ ins. in diam., 2½ ins. in diam., 30 ins. long; 24 ins. in the ground with protective ring of stone. A Larch, 6 ins. in diam., bears S69°E, 15.8 ft. dist., mkd. CN 1/16 BT; A Larch, 7 ins. in diam., bears S28°W, 6.8 ft. dist., mkd. CN 1/16 BT.
2.	Found:
	A USDA Alum. Monument, with cap 3½ ins. in diam., 6 ins. out of ground, mkd. as shown; A Western Larch, 7 ins. in diam., bears S69°E, 15.80 ft. dist., healed face; A Western Larch, 9 ins. in diam., bears S28°W, 6.80 ft. dist, healed face. A Carsonite Post with boundary tag, bears East, 7 ft. dist.
5.	Stacked and painted a mound of stone around monument; Repainted blazes and rings on all BTs; Put New BT tag on S28*W BT; Set A Steel Post with LSM & Boundary Tags, bears East, 7 ft. dist., in front of Carsonite Pos
	FOREST SEA
	S N 1/16 S29 F
	1982 2520S 2520S 2520S
	MAGNETIC DECLINATION - 16' EAST
	CERTIFICATION
	Sti Post , CURT HECKROTH East, 7' cartify information shown broken true and correct.
	S69F
	7" W Larch Confur Intelligence were the control of
	the "corner Reduction act "Ples LS" (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
	9" W Larch
	SKETCH OF CORNER
	Office of Clerk and Recorder, County of <u>Lincoln</u> . This "corner
	record" was filed for rec 229613 BOOK: CCR CCER'S PAGE: 11598 Pages: 1
	Was noted on the cross- RECORDED: 11/15/2010 11:24 KOI: CCCR'S
	TAMMY D. LAUER CLERK AND RECORDER

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

TO: GLAHE & ASSOC., INC. S.O. BOX 1863, SANDPOINT, ID. 83860,

Cross Index No. S-7 T. 35N R. 25W PMM

corner this sheet

book No. .

on the second of The second secon • .