CERTIFIED CORNER RECORDATION
Corner S¼ Sec 7 T. 35N R. 25W P.M.M. Lincoln County
1. <u>1894 G.L.O. Original Record by A.L. Jaqueth et all:</u> Set:
A Limestone, 14x8x5 ins., 10 ins. in the ground for ¼ Sec. cor. mkd. ¼ on N face; From which:
A Fir, 5 ins. in diam., bears S24°45'E, 25 lks. dist., mkd. ¼ S. BT; A Fir, 4 ins. in diam., bears N42°45'E, 33 lks. dist., mkd. ¼ S. BT;
1960 BLM Remonumentation by Cunningham: Found:
The ¼ sec. cor. of secs. 7 and 18, monumented with a limestone, 10x6x4 ins., set and mkd. as described in the official record;
From which: A Stump hole, bears S23°E, 25 lks. dist., with fallen log having illegible markings; A Stump hole, bears N47°W, 33 lks. dist., with fallen log having illegible markings;
Set: An Iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with A Brass Cap mkd. as shown;
A Fir, 7 ins. in diam., bears N70¼°E, 30 lks. dist., mkd. ¼ S7 BT; A Fir, 7 ins. in diam., bears S50°W, 16 lks. dist., mkd. ¼ S18 BT; Buried the original stone alongside and raise a mound of stone, 3 ft. base, 2 ft. high, West of
the Iron post. 1980 Certified Corner Record by Thomas C. Hill, 5612S
Found: A Brass Cap, 2½ ins. in diam., 6 ins. above ground. Mound of stone appr. 1.0 ft. West; A Douglas Fir, 6 ins. in diam., bears N73°E, 20.0 ft. dist., healed face, alive and well; A Douglas Fir, 7 ins. in diam., bears S51°W, 10.4 ft. dist., healed face, alive and well.
Painted red bands around bearing trees. 1981 Certified Corner Record by D.K. Marquardt. 2989ES Found:
A U.S. Cadastral survey Brass Cap, 2 old BT & 2 New RM's, mkd. and stamped Established:
A Douglas Fir, 8 ins. in diam., N70°E, 30¼ lks. dist.; A Douglas Fir, 8 ins. in diam., S50°W, 16 lks. dist. 2. Found:
A BLM Brass Cap, 3½ ins. in diam., 6 ins. above ground, mkd. as shown; A Douglas Fir, 11 ins. in diam., bears N73E, 20.0 ft. dist. with a healed face; A Douglas Fir, 10 ins. in diam., bears S50W, 10.4 ft. dist., with a healed face; A Douglas Fir with K Tag, bears S34E, 16.4 ft. dist., with a blaze; A Douglas Fir with K Tag, bears N34W, 16.5 ft. dist., with a snow blaze; A Fir snaq, bears N40E, 22.0 ft. dist.
1 1/ 5/
3. Established: A Steel post with LSM sign, bears East, 2.0 ft. dist. Painted blazes and bands on all BTs; Replaced tag and sign where needed. MAGNETIC DECLINATION 15*4' EAST
Fir Snag N40°E, 22.0' N34°W, 16.5' Fir Snag N40°E, 22.0' Fir Snag
N73'E, 20.0' Stil Post
East, 2' performed by the considerable in compliance with the Comer Record of the Come
S50 W, 10.4' E3 D Fir Dot 1- N C 9748 LS
SKETCH OF CORNER SKETCH OF CORNER
Office of Clerk and Recorder, County of Lincoln
record" was filed for record 229644 BOOK: CCR CCER'S PAGE: 11628 Pages: 1 Sec. 7 STATE OF MONTANA LINCOLN COUNTY STATE OF MONTANA LINCOLN COUNTY
was noted on the cross-ind RECORDED: 11/15/2010 1:23 KOI: CCER'S TAMMY D. LAUER CLERK AND RECORDER book No
TO: GLAHE & ASSOC., INC P.O. BOX 1863, SANDPOINT, ID. 83860
Cross Index No. <u>J-3 T. 35N R. 25W PMM</u> Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

corner this sheet