

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner N 1/16 S 25/ S 30 T. 35 N R. 26/25 W P.M.M. Lincoln County

Established by subdivision of Section

See Certificate of Survey 944 in Lincoln County Records

4" Doug. Fir N. 4° W. 12.7 feet Mkd with cross and BT at base

16" Larch S. 89° E. 43.7 feet Mkd. N 1/16 S30BT

Bearing tree tags affixed

Brass tags set at base of BTs at root crown distance from corner.

T35N
R26W R25W
N 1/16
S25 S30
2968 S
1981

SKETCH OF CORNER

CERTIFICATION

I, Milton I. Booth
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, _____
certify that this Corner Record correctly represents work performed
by me or under by direction in compliance with the "Corner
Recordation Act" (70-22-101, et seq., M.D.A.)

Milton I. Booth
Signature of Surveyor & Seal

Date: 8/24/81 Reg. No. 2968 S

Employer: Self


Office of Clerk and Recorder, County of Lincoln. This "corner
record" was filed for record on the Sept 1st day of 19 81,
was noted on the cross-index plat and is assigned page No. 1181 in
book No. 1

Charles L. Vaughan
County Official

Deputy

Cross Index No. S - 1 T. 35N R. 25W P.M.M.

Sec. 30



• - corner this sheet

