

- Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Reference Mon. to SW 30 T. 35 N R. 25 W P.M.M. Lincoln County Corner _

Corner was reestablished from collateral evidence found with reference to plat # 661 on file in Lincoln County, Records.

See also Certificate of Survey 944 in Lincoln County Records.

Set 3" x 30" Aluminum Post & cap on Bluff West of existing highway.

N. 1° 30' W. 46.5 feet ~10 Pine Mkd. Ref. mon.

8" Larch N. 26° W. 37.0 feet Mkd. Ref. Mon.

988

, rçır.,

N. 14º 16' 12" W. 292.04 feet to a brass cap set in Concrete Mkd. Fortine Azi.Mk.

Section Corner 25-30-36-31 falls N. 89° 39' 09" E. 450.00 feet in center of Mill Yard.

T 35N **R26W**

R25W S 30 s 36 1 S 31

Ref. Mon. 2968 \$

1981

SKETCH OF CORNER

Milton I. Booth

certify the information shown herein is true and correct.

Signature Ground Party Chief

certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (19-22-101, et seq., M.D.A.)

Signature of Surveyor & Seal


Sec.

Date: 8/24/81 Reg. No. 2968 S

Self

Office of Clerk and Recorder, County of record" was filed for record on the day of 198/, was noted on the cross-index plat and is assigned page No. book No. . County Official

Cross Index No. V - 1 T. 39N R. 25W PMM



30

· - corner this sheet

