DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found a 21 B.L.M. brass cap appr. 4" above ground. Mound of stone appr. 2.0 ft. W. Marked as shown:

From which: A 9" douglas fir bears N65°E, 48.0 ft. Healed face, alive and well.

A 14" larch bears S37°W., 26.7 ft. Scribing visible, alive and well.

1960 B.L.M. record, from found original evidence: Set a 21 iron pipe with brass cap.

From which: A larch stump 16" diam., bears S35°W., 40 lks. A 6" fir bears N66 3/4°E., 73 lks.

T35N 825 L 52+1519 1960

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 10/7/80

Painted red bands around bearing trees. Attached 1 bearing tree sign. Attached location poster to a 20" ponderosa pine which bears N66 W., 47.5 ft.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



Anthony J. Bachman

certify that the information shown herein is true and correct.

Backman

Onthone J. Bachman

Signature of Ground Party Chief

work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

T35N R25W SEC 19

= Corner recorded on the sheet

5612-S Registration Number

This "corner record" was filed for record on the 15th day of Alcember County Official assigned page No. 755 in book No. all

Cross Index No.

_{T.}35N

..... Mer. <u>r a5 v</u> 26 W

• rade ii :

- · · ·