DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set a $2\frac{1}{2}$ iron pipe with brass cap. Marked as shown:

From which: A 6" fir bears S552 W., 46 lks. A 8" fir bears $N36\frac{1}{2}$ °W., 68 lks.

Found a 2½ B.L.M. brass cap appr. 3" above ground. Scattered stones.

Marked as shown: From which: A 10" douglas fir bears S50°W., 30.3 ft. Healed face, alive and well. A 13" douglas fir bears N36°W., 44.2 ft. Healed face, alive and well.

135N RZ5 519 530 1960 BLM

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 10/8/80.....

Mounded stones appr. 2.0 ft. W. of monument. Painted red bands around bearing trees. Attached location poster to a fir on road E., appr. 300.0 ft.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



I, Anthony J. Bachman certify that the information shown herein is true and correct. Anthony J. Bachme Signature of Ground Party Chief

Thomas C. Hill certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same

Signature of Surveyor

DIAGRAM OF CORNER:

N. T35NR25W SEC 19

Corner recorded on the sheet

5612-S Registration Number

Office of Clerk and Recorder, County of This "corner record" was filed for record on the 15.11 day of December assigned page No. 957, in book No. Bell County Official Cross Index No. K-3 T 35 N

, , ē ξ, €.