(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set a $2\frac{1}{2}$ iron pipe with brass cap. Marked as shown:

From which: A 6" fir bears S50 3/4°E., 66 lks. A 7" fir bears N47 2 W., 49 lks.

Found a $2\frac{1}{2}$ B.L.M. brass cap appr. 3" above ground. Mound of stone appr. 2.0 ft. W. Marked as shown:

From which: A 10" douglas fir bears N50°W., 32.4 ft., healed face, alive and well. A 14" larch stump bears S50°E., 15.1 ft.

T35N R26W R251 518 513 BLM

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 10/8/80...

Scribed a 10" douglas fir which bears S26°E.. 23.6 ft. Marked: 1/4 S18 BT.

Attached 1 bearing tree sign.

Painted red bands around bearing trees.

Attached location poster to 7" fir which bears S34°W., 6.9 ft.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



I, Anthony J. Bachman certify that the information shown herein is true and correct.

Anthony J. Backman Signature of Ground Party Chief

Thomas C. Hill

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

T35N N. R26W R25W

= Corner recorded on the sheet

5612-5 Registration Number

Office of Clerk and Recorder, County of ________

This "corner record" was filed for record on the 15 and day of Alcember, 1980, was noted on the cross-index-plat and is

assigned page No. 758 in book No.

L. Daugha County Official $_{T}35N$

RA5W... Mer.

Cross Index No...

26 W