DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

1960 B.L.M. record, from found original evidence: Set a 21 iron pipe with brass cap. Marked as shown:

From which: A 7" fir bears N73 $\frac{1}{4}$ °E., 30 lks. A 7" fir bears S50°W., 16 1ks.

Found a 21 B.L.M. brass cap appr. 6" above ground. Mound of stone appr. 1.0 ft. W.

Marked as shown: From which: A 6" douglas fir bears N73°E., 20.0 ft., healed face, alive and well.

A 7" douglas fir bears S51°W., 10.4 ft., healed face, alive and well.

735N R25 1/4 57 518 196D $B_{L}m$

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work:....10/8/80.

Painted red bands around bearing trees.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal



correct.

> anthony Signature of Ground Party Chief

Thomas C. Hill

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

T35N R25W

= Corner recorded on the sheet

5612-S Registration Number

Office of Clerk and Recorder, County of _______ This "corner record" was filed for record on the 15th day of Desembles assigned page No., in book No. County

Cross Index No. J-3

 τ 35N

rasw Mer.

Ç: