CERTIFIED CORNER RECORDATION

Corner SEC. COR. SECS. 1, 6, 7, 12

T. <u>35N</u>. R. <u>26W</u>., PMM

LINCOLN County

RECORD:

G.L.O. 1893 Set a limestone 18x10x5 ins.....

BLM 1960

The corner of secs. 1, 6, 7, & 12 on the W bdry of Tp., monumented with a limestone 18X10x5 ins set and marked as described in the official record and witnessed by one of the original bearing trees. At the corner point—set an iron post 30" long, 2 1/2" diam, 26" in the ground, in concrete, with Brass Cap from which the remains of the original bearing tree – a larch stump 9" diam. bears N 34 ° E 116 lks dist marked BT (record)

A new bearing tree: a fir 14" diam. bears N64 3/4 °E 114 links dist mked T35N R25W S 6 BT Bury original stone alongside the iron post.

(1989) C.O.S. No.1711, found B.L.M. brass cap (1990) C.O.S. No.1781, found B.L.M. brass cap (1992) C.O.S. No.1907, found B.L.M. brass cap


FOUND:

Found a 3 1/4" B.L.M. brass cap marked as shown below, from which we found the following references:

A 24" diam. Fir tree with B.T. tag, visible scribing and red paint bears N.64 ° E., 74.5'
A 10" diam. Spruce tree with B.T. tag, visible scribing and red paint bears N.01 ° W., 138.6
A U.S.F.S. boundary post bears east 2.0'
An 8" post with B.T. tag bears S.51 ° E, 2.6'

SET

set a MDT witness post with decal 1' northerly SEE DETAIL ON REVERSE



SKETCH OF CORNER

CERTIFICATION

I, Jim Turner

certify the information shown herein is true and correct.

Signature of Gound Party Chief

I, Egnature of Gound

		Sec. IZ		
Office of Clerk and Recorder, County of LINCOLN . This	s "corner			
record" was filed for record on $9-10-03$, <u> </u>			
was noted on the cross-index plat, and is assigned Page No. 10624, in Book No.	o			
E 25 County Official		- Corner	this sh	eet

