L: \CUENTS\Department of State Lands\Fortine\Drawings\Corner Recors.dwg

CERTIFIED CORNER RECORDATION

Corner	SW 1/16	Section 36	т	35N	R	26W	P. M. M	LINCOLN	County
					10.				

G.L.O. Record:

This interior section subdivisional corner was never set by G.L.O. or other original government survey, but its position can be calculated by dimensions shown on the official government plat for this township.


Subsequent Record:


No subsequent record.

<u>New Monumentation Established:</u>

At the calculated position for the corner, as established by proportionate measure and as shown on the attached section subdivisional diagram, I set a Berntsen flared base monument (model #A1NBF30), which consists of a 2-3/8" diameter by 30" long flared aluminum pipe with a magnet and 3-1/4" diameter aluminum cap attached to the top, stamped as shown in detail below. Position for corner falls in a cultivated field, therefore monument was set so that the top of cap is buried 15" below the ground surface.

Section Subdivision Section 36, Township 35 North, Range 26 West





SKETCH OF CORNER

Signature of Sureyor & Seal

Office of Clerk and Recorder, C	County of Lincoln	This "corner	Sec. 36		
record" was filed for record s	190090 BOOK: CCR CCER'S	PAGE: 10891 Pages: 1			
, C	MECORDED: 12/05/2005 2:19 KOI: CORAL M. CUMMINGS CLERK AND RECO				
	TEE: \$0.00 BY:	P.O.BOX 7323, KALISPELL, MT			
	Cross Index No. Y-22 T. 3	35N R 26W PMM			
Adopted July 1, 1981, Monta	ana Board of Professional Engineers	& Land Surveyors	•=corner	this :	sheet

