

# CERTIFIED CORNER RECORDATION

Corner CE 1/16 Sec 13 T. 35N R. 26W P.M.M. Lincoln County

## 1. Original GLO Notes:

This corner was never set.

## 2. Found:

None.

## 3. Established:


Set a 3 1/4 inch Aluminum cap on 5/8 inch rebar 0.4 ft. above ground stamped as shown.

A D. Fir, 8 ins. in diam. bears S3°W, 37.8 ft. dist., scribed CE 1/16 S 13 BT.

A D Fir, 13 ins. in diam. bears S62°W, 20.5 ft. dist., scribed CE 1/16 S13 BT.



MAGNETIC DECLINATION - 15°4' EAST



13" D Fir  
S62°W, 20.5'



8" D Fir  
S3°W, 37.8'

## CERTIFICATION

I, Erich Shrock  
certify the information shown herein to be true and correct.

LAWRENCE A. GLAHE  
I, LAWRENCE A. GLAHE  
certify that the corner location shown herein represents the  
corner as established in compliance with the  
"Corner Recordation Act" (MCA, 82-1-101, et seq.)

Date: 12/6/10 9748 LS  
Employer: GLAHE & ASSOC., INC.

## SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner

record" was filed for re 230123 BOOK: CCR CC&R'S PAGE: 11721 Pages: 1

was noted on the cross STATE OF MONTANA LINCOLN COUNTY  
RECORDED: 12/09/2010 12:44 KOI: CC&R'S

book No. TAMMY D. LAUER CLERK AND RECORDER

FEE: \$0.00


BY: LAWRENCE A. GLAHE

TO: GLAHE & ASSOC., INC. P.O. BOX 1863, SANDPOINT, ID. 83869

Cross Index No. L-24 T 35N R. 26W PMM

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Sec. 13



● corner this sheet

1947

1948

1949

1950