## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record, set post. Fir. 24" S 33 45' E 28 lks. Fir. 36" N 43 30' E 72 lks.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7-13-73

3"Place "/ BT Tag

Bross Cap

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Barnaby Lake Properties - Units No. 1 &2

Office of Clerk and Recorder, County of

Surveyor's Seal		DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.	N.T. 35 N R 26W
•	Signature of Ground Party Chief	,,
	1. D.K. Marguard+	28
* ************************************	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	
	DC Magnedic Signature of Surveyor	S= Corner recorded on the sheet
	ES 2989	
	Registration Number	

Porm 125—41328

Assigned page No. 1194, in book No. | Skene J. Jaugher, hy Bett, Bell, County Official Sepurt, County Official Sepurt, County Official Mer.

• · . . ·