

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner Section Corner - Sec. 14, 22 E 23 T. 35N R. 26W P.M.M. Lincoln County

Record: Set a post 4' long x 4" sq. 24" in the ground from which:

a fir 6" diam. bears N. 39° 30' E. 21 Ks.

a fir 6" diam. bears S. 51° E. 22 Ks.

a fir 6" diam. bears S. 74° 30' W. 27 Ks.

a fir 6" diam. bears N. 28° W. 20 Ks.

No evidence of original corner found.

Found axle set by Haskell - Accepted as corner.

See C.O.S. No 800 for adjoining corners.

### CERTIFICATION

I, \_\_\_\_\_  
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, D.K. Marquardt

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

D.K. Marquardt  
Signature of Surveyor & Seal

Date: 7-8-81 Reg. No. 2383ES

Employer: \_\_\_\_\_

### SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner

record" was filed for record on the 12<sup>th</sup> August day of 1981,


was noted on the cross-index plat and is assigned page No. 1208, in

book No. 1

Edmund L. Taughan, by Betty Bell  
County Official deputy

Cross Index No. 12-17 T. 35N R. 26W PMM

Sec. 14



• corner this sheet

