

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## • CERTIFIED CORNER RECORDATION


Corner Sec. Cor. - Sections 11, 12, 13 & 14 T. 35N R. 26W P.M.M. Lincoln County

Record: Set a post 4' long 4" sq. with marked stone  
12" in the ground.  
Dug pits for Rms.

No original evidence found.

Set aluminum cap at intersection of E-W fence line  
with N-S E of Graves Creek Rd.

See C. of S. No 800 for adjacent corners.



SKETCH OF CORNER

### CERTIFICATION

I, \_\_\_\_\_  
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, D.K. Marquardt  
certify that this Corner Record correctly represents work performed  
by me or under by direction in compliance with the "Corner  
Recordation Act" (70-22-101, et seq., M.D.A.)

D.K. Marquardt  
Signature of Surveyor & Seal

Date: 7-8-81 Reg. No. 2989ES


Employer: \_\_\_\_\_

Office of Clerk and Recorder, County of Lincoln. This "corner  
record" was filed for record on the 12<sup>th</sup> August day of 1981,  
was noted on the cross-index plat and is assigned page No. 1209 in  
book No. 1

Deborah L. Vaughn, by Betty Bell  
County Official Deputy

Cross Index No. J-21 T. 35N R. 26W P.M.M.

Sec. 14



• corner this sheet

