INSTRUCTIONS

quent record used to evaluate the corner position.

ce found, note discrepancies in the record, state method of establishing

- 5. Sketch or corner, show all pertinent data which can best be shown in a sketch example, cortopography ites, position of accessories, etc.

 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner WC SW 1/16 Sec. 6

T.35N

P.M.M. Lincoln

County

No previous record of corner monumentation on file.

FOUND:

RECORD:

Nothing to show evidence of a previously monumented corner.


A 34" diam., aluminum F.S. line marker cap on 10 feet of 5/8" diam. aluminum section pipe, approx. 2" exposed and surrounded by mound of stone.


from which

A fir, 15" diam. bears N.29°E.,225@6ffeet dist., scribed"MWCUBT".

A fir, 8" diam., bears S.73°E., 61.5 feet dist., scribed "WC BT".

Note: The actual position of the SW 1/16 corner falls in Lost Lake, therefore in order to mark the boundary line a WC was set.





\$50 15"FIR CERTIFICATION James W. Reed Signature Gro Thomas C. Hill LOST certify that this Corner Record correctly represents work performed LAKE by me or under by direction in compliant Recordation Act" (79 22-101, et seq., M.D.A.) 3/15/83_{Reg. No.} 5612 S 541/16 Employer: U.S.F.S **SKETCH OF CORNER**

Office of Cl	erk and Recorder, Count	voi Lincoln	This ''corner	Sec.	6
	s filed for record on the	Uwy 10th	day of 1983		
was noted o	n the cross-index plat an	nd is assigned page No	975 in		 -
book No		Janet BF Siegel by County Offi	Letty L. Conces		<u> </u>
		County Offi	acquisig		

т. <u>35</u> г. <u>26</u>

corner this sheet

· . . A STATE OF THE STA . .