CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) COMMON CORNER FOR SECTION 4,5,8 & 9, T.35N., R.26W,P.M.M. LINCOLN COUNTY, MONTANA

Found Brass cap and Bearing trees; (Record) Iron post, 30" Long, 2 1/2" DIAM., 26" IN THE GROUND, WITH BRASS CAP MARKED.

A FIR, 12" DIAM., BEARS N 15 1/2°E, 20 LINKS DISTANCE, MARKED T 35N. R.26W, S.4 BT A FIR, 14" DIAM., BEARS S 36 1/2° E, 6 LINKS DISTANCE, MARKED T 35N.

R. 26W, S 9 BT

A PINE, 10" DIAM., BEARS S 21 3/4° W, 48 LINKS DISTANCE, MARKED T 35N.

R. 26W, S 8 BT

A PINE, 8" DIAM., BEARS N 31 3/4° W, 100 LINKS DISTANCE, MARKED T 35N.

BT ---Bury original stone alongside the IRON POST.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work UG. 7, 1973

THE MONUMENT AND BEARING TREES WERE NOT CHANGED

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

IS" PINE WITH BLAZE 12" PINE WITH BLAZE GOD NAIL F TAG T35N, R26W 55BT 60-D NAIL 15" PINE WITH BLAZE 6050 NAIL

Surveyor's Seal

I, ROBERT E. certify that the information shown herein is true and correct. Robert &


Sann Signature of Ground Party Chief

I, JAMES L. HAHN certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

James L. Haller

2795 S Registration Number



= Corner recorded on the sheet

Office of Clerk and Recorder, County of Juneals Cluquet 19.74, was noted on the cross-index plat and is This "corner record" was filed for record on the day of

346 , in book No

Cross Index No. E 9 T. 35

•