INSTRUCTIONS

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner S. 1/16 Section 27 & 26 T. 35 N. R. 26 W. P.M.M. Lincoln

_County

corner this sheet

RECORD:

Unrecorded Donald V. King Jr. (M.L.S. No. 5212-S) survey done in area. FOUND:

No evidence of unrecorded S 1/16 corner by King found in area.

MAINTENANCE:

Set a 5/8 inch diam., 24 inch long rebar with yellow P.V.C. cap stamped: KED 4975-S for S. 1/16 corner.

We established two BT's described as follows:

A 12 inch diam Douglas fir bears N.68°E., 6'2.7 feet scribed "S.1/16 S. 26 BT."

A 12 inch diam Douglas fir bears S.42°E., 56.2 feet scribed "S.1/16 S. 26 BT.

Placed BT and Land Survey Monument signs.

Painted Blazes red.

Painted a 6 inch red band around the trees above the BT signs.

Set a 6 foot steel post 2 feet in the ground, 2 feet East of corner and attached Land Survey Monument sticker to it.

SEC. 27 SEC. 26 STG CORNER 12" Douglas FIR BT. 12" Douglas FIR BT.	certa that his Corne Art Ord correctly represents work performed by red or under my direction in compliance with the "Corner Recognition Act" (470-22-10) Cet seg. M. G.A.)
SKETCH OF CORNER (2)	
Office of Clerk and Recorder, County of Juneah . This "corner record" was filed for record on Jan 30, 1981	
was noted on the cross-index plat and is assigned page No. $\frac{44/3}{3}$, in	
book No But Mountains by But But But Sure for County Official	

