

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography lies, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner $\frac{1}{4}$ Section 28-27 T. 35 N. R. 26 W. P.M.M. Lincoln County

RECORD: 1894 Sizer Survey

Set a quartzite stone 14x10x5 inches, 10 inches in the ground for $\frac{1}{4}$ Section corner marked $\frac{1}{4}$ on West face, from which.

A fir 16 inches diam. bears N.45°E., 20 links (13.20 ft.) dist., marked $\frac{1}{4}$ S. BT.

A fir 14 inches diam. bears N.30°W., 29 links (19.14 ft.) dist., marked $\frac{1}{4}$ S. BT.

FOUND:

No evidence of original Sizer survey found on ground.

A 2 inch diam. galvanized iron pipe with no cap set by 2989-ES per corner recordation form No. 1145.

MAINTENANCE:

From the accepted position of the $\frac{1}{4}$ corner by 2989-ES we established two BT's described as follows:

A 12 $\frac{1}{2}$ " inch diam. Douglas fir bears N.54°30'W., 7.3 feet scribed " $\frac{1}{4}$ S. 28 BT"

A 7 inch diam. Douglas fir bears N.53°30'E., 9.6 feet scribed " $\frac{1}{4}$ S. 27 BT."

Placed BT signs and painted the blazes red.

Painted a 6 inch band around the trees above the BT signs.

<p>12$\frac{1}{2}$" Douglas FIR BT.</p> <p>N.54°30'W. 7.3</p> <p>N.53°30'E. 9.6</p> <p>7" DOUGLAS FIR BT.</p> <p>1/4 CORNER BY 2989-ES</p> <p>SEC. 28</p> <p>SEC. 27</p> <p>OLD FENCE LINE</p> <p>SKETCH OF CORNER</p>	<p>CERTIFICATION</p> <p>I, <u>JOHN DAMON</u></p> <p>certify the information shown herein is true and correct.</p> <p><u>[Signature]</u></p> <p>Signature of Land Surveyor</p> <p>I, <u>E. J. DAVIS</u></p> <p>certify that this Corner Record Form represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-04, et seq., M.C.A.)</p> <p><u>4975 S</u></p> <p>Signature of Surveyor's Seal</p> <p>Date: <u>1/30/91</u></p> <p>Employer: <u>DAVIS Surveying & Inc</u></p>
---	---

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Jan 30, 1991 was noted on the cross-index plat and is assigned page No. 4415, in book No. _____

Coral M. Cummings by Bill Brinkhoff
County Official

Sec. 27

Cross Index No. _____ T. _____ R. _____ PMM

• - corner this sheet

