
INSTRUCTIONS

subsequent record used to evaluate the corner position.



- corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner E. 1/16 Section 27 T. 35 N. R. 26 W. P.M.M. Lincoln _County

RECORD:

Unrecorded Donald V. King Jr. (M.L.S. No. 5212-S) survey done in area.

FOUND:

A 5/8 inch diam. rebar and P.V.C. cap stamped: KING 5212-S purported to be E. 1/16 corner out of position.

MAINTENANCE:

Set a 5/8 inch diam., 24 inch long rebar with yellow P.V.C. cap stamped: KED 4975-S for E. 1/16 corner.

We established two BT's described as follows:

An $8\frac{1}{2}$ inch diam. Douglas fir bears S.84°15'W., 12.7 feet scribed "E. 1/16 S. 27 BT."

A $7\frac{1}{2}$ inch diam. Douglas fir bears S.26°E., 22.3 feet scribed "E. 1/16 S. 27 BT."

Placed BT signs and painted the blazes red.

Painted a 6 inch red band around the trees above the BT signs.

SEC. 27	CERTIFICATION 1. ON A DAMON certify the information thousand correct.
E 16 CORNER	Ignature Ground Pirty thief I. Certify that the Corner Record orrectly represents work performed by me caluadir my director in compilative with the "Corner Recordation Act," (70-20 00) 51 Seq., M.C.A. (1)
B1" Douglas Fir. BT. SKETCH OF CORNER	Date: Davis Survey of Seal Employer: Davis Survey of Su
Office of Clerk and Recorder, County of	Sec. 27 This "corner
was noted on the cross-index plat and is assigned page No. 44/ book No. Cocal M Cummung County Offici	sby Bir Bushel
Cross Index No.	RPMM • - corner this sheet

. . • · •. .