

CERTIFIED LAND CORNER RECORDATION

1/4 Corner - between Sec's. 4/3 Twp. 35N., R.26W., M.P.M.

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Original record: N 0°03'W between Secs 3 & 4 random---(intersect Twp. line)
thence S 0°08'W between Secs. 3 and 4 16.46 Griffiths Creek, 22 lks.
wide Course West; 40.16 Set a post (3"x3") for 1/4 cor. from which
a 12" Fir bears S52°E 43 lks.
a 12" Fir bears N63°30'W 44 lks.

EVIDENCE FOUND - None

An exhaustive search failed to disclose any evidence to define the location.
Corner on Twp. line is Std. Brass Tablet - Southeast corner of Sec. 4 is
Std. pipe monument from which brass tablet has been removed.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 1965

See sketch on reverse side.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY:
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Reverse Side.

Surveyor's Seal

I, J. W. Ninneman

certify that the information shown herein is true and correct.

J. W. Ninneman
Signature of Ground Party Chief

J. W. Ninneman

I, _____
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

J. W. Ninneman
Signature of Surveyor

DIAGRAM OF CORNER:

N.

1/6 Cor.

1/4 Cor.

4 1/3

○ = Corner recorded on the sheet

Montana 534 E.S.
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of April 1966, was noted on the cross-index plat and is
assigned page No. 51, in book No. 1

ELEANOR L. VAUGHN, *Eleanor L. Vaughn*

County Official

B-13

C-13

35

R. 26

Cross Index No. T. Mer.

$\frac{1}{4}$ Corner-between Sec's. 4/3 Twp. 35N., R.26W., M.P.M.

Steel Bar for 1/16 Corner
A 10" crooked Fir
Bears N 14°W 15.3' →
Marked corner 1/16

Steel Bar for corner
A 9" Pine stump east on line
Marked Cor. 4'

Steel Bar on line
A 5" Pine bears---
S 13°30'W 8'
Marked Corner 8'

Set a 3/4" steel rod for 1/4 Corner
alongside of a 4" lodgepole pine
cut off at 3 1/2 feet above ground
Squared on N., E., and S.
A 7" pine bears S 69°W 7.8 ft.
A 7" pine bears N 65°30'E 13.5 ft.
Both tagged with BLM BT signs

On line between said Sec's. 4 & 3 at 2640 feet north of the southeast corner of said Sec. 4 - set a 3/4" steel rod for 1/4 Cor. alongside of a 4" lodgepole pine cut off at 3 1/2 ft. above ground, squared on N,E & S, from said 3/4" Rod a 7" Pine bears N65°30'E 13.5 feet marked 1/4 S 3 BT.* Both tagged with Std. B.T.Signs.

On line between said Sec's. 4 & 3 at 820 feet north of $\frac{1}{4}$ Cor.
set a steel "T" bar from which a 5" Pine bears S $13^{\circ}30'W$ 8 feet.
Marked Corner 8'

On line between said Sec's. 4 & 3 at 1320 feet north of the 1/4 Corner set a steel "T" bar for 1/16 Corner from which a 10" crooked Fir bears N 14°W 15.3 feet marked 1/16

* A 7" Pine bears S69° W 7.8 Feet

Filed this 4th day of April A. D. 1966
at 11:25 A. M.
Edward J. Laughlin
Clerk
By: Max Peterson, Deputy