(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found a  $2\frac{1}{2}$  iron pipe approximately 3" above ground with brass cap marked as shown. Collar of stone.

From which: A 9" lodgepole pine bears N 29 W, 8.8 ft., scribing visible

1970 Record: Monument as above and stamped as shown.

From which: A 10" lodgepole pine bears N 32°W, 9.0 ft. A 6" lodgepole pine bears S 7°W, 16.5'

\* Set by proportionate measurement (1970)



DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

TO PERPETUATE & REPLACE DESARDYED 1970 6"Z.P.NE Date of work: 5/80 SCRIBED ANEWA 6" lodgepole pine bears N 64 E, 13.3 ft., marked \( \frac{1}{4} S3 BT. \)

Painted red bands around BT's.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Reverse Side.

THOMAS C.

HILL

5612 S

SURVE

Surveyor's Seal

Anthony J. Bachman

certify that the information shown herein is true and correct.

Inthony 4. Uacam Signature of Ground Party Chief

I, Thomas C. Hill

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

5612S Registration Number DIAGRAM OF CORNER:

N. T35N R26W

1 1/4

S4 S3

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Sunces of October 1989, was noted on the cross-index plat and is assigned page No. 874, in book No.

County Official Supers

Cross Index No. 13-C T. 35 N. R. 26 N. Mer.

Section 3, Township 35 North, Range 26 West, P.M.M.

## Legend:



