

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

FOUND A 1/2" REBAR w/ PLASTIC CAP STAMPED "2989 ES"
AS PER CERTIFICATE OF SURVEY NO. 567

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 6/2/80

SET A 2 1/2" X 30" ALUMINUM PIPE APPROX. 18" IN GROUND
w/ ALUM CAP MARKED AS SHOWN, RAISE A MOUND OF STONE
AROUND PIPE, LOCATED ON SIDE OF EARTH FILL.

FROM WHICH: POLE # D6AC3 (UNDERGROUND TELEPHONE CABLE)
BEARS S 74° E, 41.3 FT.

W 1/16 + 33
3612 S
1980

* LOCATED WEST ON MUD CRK RD. APPROX. 0.25 MILE FROM INTERSECTION
WITH US HWY 93.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE REVERSE SIDE

REBAR AS NOTED ABOVE BEARS S 5° 30' 20" W, 0.83 FT.

THE REBAR WAS NOT ACCEPTED BECAUSE IT'S POSITION WAS CONTROLLED
BY THE LOCATION OF THE SE CORNER OF SECTION 3, WHOSE POSITION
WAS DETERMINED TO BE IN ERROR.

Surveyor's Seal



I, ANTHONY J. BACHMAN
certify that the information shown herein is true and
correct.

Anthony J. Bachman
Signature of Ground Party Chief

I, THOMAS C. HILL
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Thomas C. Hill
Signature of Surveyor

DIAGRAM OF CORNER:

N. T35N R26W
1
W 1/16 SEC 3
SEC 10

● = Corner recorded on the sheet

5612 S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 8th day of October, 1980, was noted on the cross-index plat and is
assigned page No. 897, in book No. _____

Thomas J. Douglas, Jr.
County Official

Cross Index No. 14-E T. 35 N R. 26 W Mer.

