	CERTIFIED CORNER REC	CORDATION
Cor	10 11 rner <u>Sec. cor. secs. 15 14</u> <u>T 36 N.</u> R. 26	W. P.M.M. LINCOLN County
I. Record: 1893 Original Record by Peter M. Cardell & Abrahm L Jaqueth; 80.00 chains. Set a limestone 12x12x12 ins., 8 ins. in the ground for Cor. to Secs. 10, 11, 14 & 15, marked with 4 notches on S. and 2 notches on E. sides from which: A pine, 13 ins. diam., N53'E, 40 lks., marked T36N R26W S 11 BT. A tamarack, 14 ins. diam., S63'30'E, 35 lks., marked T36N R26W S 14 BT. A pine, 13 ins. diam., S4'W, 23 lks., marked T36N R26W S 15 BT. A fir, 12 ins. diam., N79'30'W, 31 lks., marked T36N R26W S 10 BT.		L Jaqueth; 80.00 chains. Set a
		T36N R26W S 14 BT. 5W S 15 BT.
1982 Certified Corner Recordation by T.C. Hill:		
Found: Mound of stones from which. A 22" larch bears S64°E, 23.26 ft., healed face. A 24" larch bears N79°30'W, 20.46 ft., healed face. Set: A 30" Forest Service aluminum pipe approximately 28" in the ground, with an aluminum cap marked as shown, with a stone collar. From which:		
		in the ground, with an aluminum cap
		/ \
	A 24" larch bears S61"W, 8.4 feet, inscribed S 15 BT. A 22" larch bears S62"E, 22.9 feet, inscribed S 14 BT A 30" fir bears S74"E, 18.2 feet, inscribed S 11 BT. A 22" fir bears N61"E, 34.5 feet, inscribed S 10 BT.	S10 S11 S15 S14 5612S 1981
II. Found a 2 $\frac{1}{2}$ in. diam. aluminum pipe, 2 ins. above ground with a 3 $\frac{1}{4}$ in. diam. aluminum marked as shown above, from which:		with a 3 $\frac{1}{4}$ in. diam. aluminum cap
	A larch, 24 ins. diam., S62°E, 22.9 ft. dist., marked wat A larch 26 ins. diam., S61°W, 8.4 ft. dist., marked with A fir snag, 30 ins. diam., S74°E, 18.2 ft. dist., marked (NOTE: wrong section on bearing tree.) A fir snag, 24 ins. diam., N61°W, 34.5 ft. dist., marked	h a healed face. d S 11 BT.
Establish two new bearing trees: A fir, 10 ins. diam., N61°E, 29.1 ft. dist., marked T36N R26W S 11 BT. A fir, 8 ins. diam., N44°W, 19.6 ft. dist., marked T36N R26W S 10 BT.		
III.	III. Attached Bearing Tree and Land Survey Monument signs to the bearing trees. Painted red bands around the bearing trees.	
Date of Fieldwork: 9/18/2002 Survey crew: Steve Boyer, Tom Hommel Magnetic declination: 20° East assumed Equipment used: Hand compass and loggers tape U.S. Forest Service, Supervisiors Office, 1101 Hwy. 2 West, Libby, MT 59923 (406) 293—6211		.ibbv. MT 59923 (406) 293–6211
	A	CERTIFICATION
	A A A A A A A A A A A A A A A A A A A	steven A. Boyer 9750 54V certify the information showly begain in true one correctly Signature Found Party Chief N
STAT 182 II		certify that this corner Record correctly represents work performed by me or underly direction in corner recordation Act 100 23 15th et est. M.C.
Date: 09/18/2002 Reg. No. 13769LS SKETCH OF CORNER NOT TO SCALE Employer: U. S. Forest Service		
NOT TO SCALE		
Office of Clerk and Recorder, County of Lincoln This "corner Sec. 15		
record" was filed for record on		
was noted on the cross-index plat and is assigned page No. 10000 in book No.		
County Official		

Cross Index No. <u>J-17</u> T. <u>36N. R. 26W.</u> P.M., MT

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

• corner this sheet