

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

-CERTIFIED CORNER RECORDATION

Corner Sec. 22, Sections 15, 16, 21, 22 T. 36N R. 26W P.M.M. Lincoln County

Record:

Set a post 4' long 4" square 24" in the ground from which:

- a tamarack 24" diam. bears N. 43° 30' E. 331 Ks.
- a tamarack 22" diam. bears S. 26° E. 261 Ks.
- a tamarack 14" diam. bears S. 26° W. 231 Ks.
- a fir 8" diam bears U. 18° W. 141 Ks.

No evidence of original corner found.

Found iron pin - accepted as corner.

See C. of S. No. 915 for adjacent corners."

CERTIFICATION

I, _____
certify the information shown herein is true and correct.

Signature Ground Party Chief

I, DK. Marguardt

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

DK. Marguardt
Signature of Surveyor & Seal

Date: 7-15-81 Reg. No. 2283ES


Employer: _____

SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 17th day of 1981, was noted on the cross-index plat and is assigned page No. 1104, in book No. 1

Alvan L. Vaughn, Jr. by Debbie Bell
County Official Deputy

Sec. 22



Cross Index No. N-13 T. 36N R. 26W P.M.M.

• - corner this sheet