

- INSTRUCTIONS**
1. Original and/or subsequent record used to evaluate the corner position.
 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
 3. Description of monument and accessories set to perpetuate the corner position.
 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, triangulation line, position of accessories, etc.
 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

27
Corner 1/4 34 SEC. 27 T. 36N R. 26W P.M.M. Lincoln County


R RECORD: Original G.L.O. survey 1893.

From B.L.M. remon. notes.

The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, =monumented with a sandstone, 18"X10"X6", firmly set and mkd. $\frac{1}{4}$ on the N. face, and witnessed by the remains of the original bearing trees.

at the point

Set an iron post, 30" long, $2\frac{1}{2}$ " diam., 29" in the ground, in concrete, with brass cap mkd.



from which

the remains of the original bearing trees:

A stump 18" diam., bears N 14° E, 90 lks. dist., visable marks BT. (RECORD)

A stump, 18" diam., bears S 52° W, 22 lks. dist., visable marks BT. (Record: S56 W, 22 lks.)


The new bearing trees:

A fir, 7" diam., bears N $37\frac{1}{2}^{\circ}$ E, 52 lks. dist., mkd. $\frac{1}{4}$ S27 BT.

A fir, 7" diam., bears S $13^{\circ}45'$ E, 22 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

Bury the origional stone alongside and raise a mound of stone, 3 ft. base, 2 ft. high, N of iron post.

FOUND: B.L.M. brass cap described and marked as shown, above, the two B.L.M. 7" (now 8") fir bearing trees with healed faces in position as shown above, and the two 18" stumps with visable marks and in position as shown above.



() 8" FIR

N 37 1/2 E
34.3

() 8" FIR

SKETCH OF CORNER

CERTIFICATION

I, James W. Reed

certify the information shown herein is true and correct.

James W. Reed
Signature Ground Party Chief

Thomas C. Hill

I certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (T.S. 29-101, et seq., M.D.A.)

Thomas C. Hill
Signature of Surveyor & Seal
Date: 3/15/83 Reg. No. 5612 S.
Employer: U.S.F.S.

Office of Clerk and Recorder, County of Lincoln This "corner


record" was filed for record on the June 16 day of 1883

was noted on the cross-index plat and is assigned page No. 2253, in book No. _____

Jinet BF Siegel by Betty L. Conces
County Official

Cross Index No. V-15 T. 36 R. 36 P.M.M.

Sec. 27



* corner this sheet