

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Not Previously Set

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Nov. 1975

Date of work:

Set USFS: Brass Cap at the proper location for E 1/16 S 17 S 20, from which:

A Tamarack 18" diam. bears North 6.28'

A Tamarack 16" diam. bears S 65° E 7.33'

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 181.

Surveyor's Seal

I, S. R. Smith
certify that the information shown herein is true and correct.

S. R. Smith
Signature of Ground Party Chief

I, Dean K. Marquardt
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Dean K. Marquardt
Signature of Surveyor

DIAGRAM OF CORNER:

N. T 36 N
S 17
S 20 E 1/16
R 26 W

= Corner recorded on the sheet

ES2989
Registration Number

Office of Clerk and Recorder, County of

This "corner record" was filed for record on the day of 19, was noted on the cross-index plat and is

assigned page No. 396, in book No.

County Official