CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Not Previously Set

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Nov. 1975

Set USFS Brass Cap at the proper location for W1/16 $\frac{s}{s} = \frac{17}{20}$, from which:

A Fir 14" diam. bears N78° W 36.69' A Fir 6" diam. bears S10° W 23.9'

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 181.

ressigned page No. 466 in book No. 1

Surveyor's Seal	S. R. Smith	DIAGRAM OF CORNER
	certify that the information shown herein is true and correct. Signature of Ground Party Chief	N. $T36N$ $S/7$ $S20$
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Signature of Surveyor	R 26 W = Corner recorded on the sh
	ES2989 Registration Number	

Cross Index No. N-6 T. 36 N R. 26 W Mer.