

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

GLO Record: Set a post, from which: A 6" Pine bears N 54° 30' W 12 lks.
An 8" Pine bears S 4° E 25 lks.

BLM Record (1959 Remonumentation): Found disintegrated post and remains of the original bearing trees. Set a Brass Cap from which:

The remains of the original bearing trees:
A 10" dead Pine bears S 2 1/2° E 25 lks, marked 1/4 S BT
A 10" Pine bears N 44 1/2° W 12 lks, marked 1/4 S BT

The new bearing trees:
A 7" Pine bears S 10 1/2° E 21 lks.
A 7" Pine bears N 5 1/4° W 47 lks.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1975

Found: BLM Brass Cap, original BT's and new BLM BT's, as described above

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 152

Surveyor's Seal

I, S. R. Smith
certify that the information shown herein is true and correct.

S. R. Smith

Signature of Ground Party Chief

I, Dean K. Marquardt
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Dean K. Marquardt

Signature of Surveyor

DIAGRAM OF CORNER:

N. T 36 N
S 17.
S 20 1/4
R 26 W

= Corner recorded on the sheet

ES2989

Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 28th day of January 1976, was noted on the cross-index plat and is

assigned page No. 404, in book No. 1

Elaine L. Thugha, Mpe Watson, Deputy
County Official