CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record: Set red sandstone 14 x 12 x 10 10" in the ground, marked 1/4 on West from which:

rom which:

A 5" Fir bears S 27°E 28 1ks. A 10" Fir bears S 80° W 67 1ks.

Found: Sandstone still firmly in place and properly marked.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

July, 1975

Date of work:...

Cross Index No. T-/ T. 36N R. 26 W Mer.

Since the stone is still firmly set, we did not remonument it. We set two new bearing trees as follows:

A 12" Ponderosa Pine bears N12°W 29.37' A 10" Ponderosa Pine bears S 29°W 9.24'

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey # 152

FORM 125 - 41605

	DIAGRAM OF	C 10 C 11	
	3 7 .	I, S.R. Sm:+h certify that the information shown herein is true and	Surveyor's Seal
	и. З	correct.	
	, r	I R Smith	
\$ 30	N. 3 Y S 25	Signature of Ground Party Chief	
;	" > 1		
	9 .	ı, Dean K. Marquardt	
b	m	certify that I have carefully performed or reviewed the	
,	K	work done on the diagrammed corner as reported on this	
		recordation form and approve the same.	
on the s	= Corner recorded	Dlan X Harginall .	
		Signature of Surveyor	
		ES2989	
		Registration Number	
on	= Corner recorded	Dlan X Hlarguarde Signature of Surveyor ES2989	