

# CERTIFIED LAND CORNER RECORDATION

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record: Running East from the SW corner of Section 30, 30.00 (chains), on top of cut bank 170 ft. above right bank of Tobacco River, Set a sandstone 22 x 12 x 6 ins. 17 in. in the ground for Witness Cor. to 1/4 sec. cor. marked WC 1/4 on N. face from which

A Pine 9" diam. bears N 7° E 17 lks. dist. marked WC 1-4S. B.T.  
A fir 14" diam. bears N 29° W 47 lks. dist. marked WC 1-4S. B.T.

Found: We found a 17" fir with scribing as called for in the original notes; however, the blaze faces approximately S 50° E (South 29° East Rec.) We also found the remains of a 10" pine: Scribing was fully visible on scattered remnants lying around a rotted stump. The original direction of the blaze was impossible to determine.

## DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: June, 1975

We used the pine stump to set the corner and disregarded the fir, as the blaze on the fir does not fit the record. Note that the resultant measured bearing from the re-established corner to the pine B.T. is the same numerically as the record distance. (Rec. = N 29° W 47 lks. Fd. = N 47° W 76.35') The corner as we set it is six feet back from the edge of a cut bank and commands a clear view of the valley to the east, whereas if the fir B.T. were used to establish the corner, it would be set back too far West to see into the valley to continue the original section line. Finally, note that the corner as set faces the blaze on the fir B.T. It should also be noted that at the W 1/16 S 25, we found an old blazed tree with a scribed face, "1/16 B.T." even though the G.L.O. set no 1/16 corner here. The same person who scribed this tree probably scribed the misplaced fir at the Witness corner, neither one of which are therefore G.L.O.

## SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

At the Witness Corner, we set a 2" x 30" iron pipe and brass cap, from which:

A 4" Pine bears Northwest 19.35'  
A 5" Pine bears South 16.95'  
A blazed and scribed 17" fir bears N 47° W 76.35'  
The remains of a 10" Pine bear N 7° E 11.40'

Surveyor's Seal

S. R. Smith

I, \_\_\_\_\_  
certify that the information shown herein is true and correct.

*S R Smith*

Signature of Ground Party Chief

D. K. Marquardt

I, \_\_\_\_\_  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

*D K Marquardt*

Signature of Surveyor

## DIAGRAM OF CORNER:

N. *T 36 N*  
*S 30*  
*S 31* — W.C.  
*R 26 W*

— Corner recorded on the sheet

ES 2989

Registration Number

Office of Clerk and Recorder, County of *Lincoln*

This "corner record" was filed for record on the *28th* day of *January*, 19*76*, was noted on the cross-index plat and is assigned page No. *422*, in book No. *1*

*Charles L. Taylor*  
County Official