INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.

CERTIFIED CORNER RECORDATION						
se 1/16 of s33					Lincoln	
Corner	T	•	.R	P.M.M		County
. No previous record.						
I. No evidence found.	•					
II. At the calculated postion	, set a 3/4 in. di	am., 30 ins.	long,	alum. rod 24 ins.	in the ground wi	ith alum. cap
mkd. as shown.						
		<i>(</i> :				
		SE 1/16 \$33	}			
	/	9008Ls 1992				
		\ '''				
From which						
A fir, 9 ins. diam., A larch. 9 ins. diam	bears N18 E, 20.6 ., bears N80 E, 21	ft. dist., m .0 ft. dist.,	kd. SE mkd.	1/16 S33 BT. SE 1/16 S33 BT.		
Painted red bands around Set a 6 ft. galvanized st						
Magnetic Declination: 20	East	n band survey	marke	and Property Bot	indary decais, we	est, 3 It.
						01:744
					•	OI'ALD A
						PCAREON SCOELS
					: (7	ر ٥ م
					1.	CALERY O
					*****	URVE
	A 011 = 0			1	·	
	1 49"FIR			Kawin	CERTIFICATION A. Todd	
				[', 	ition shown herein is true	and correct.
	\$79.	1		Ken	i A Tool	2
	N80°E	£9"Z	ARC.H		Signature Ground Party Cl d A. Pearson	hlef
	21.0 F	7		certify that this Cor	ner Record correctly repre	
				Recordation Act" (ny difection in complian 70-22-101, et seq., M.C.A	ice with the "Corner
					Signature of Surveyor & S	eal
				10/1/		

SKETCH OF CORNER

Sec. 33 Office of Clerk and Recorder, County of _ $_{-}$. This ''corner record" was filed for record on __ was noted on the cross-index plat and is assigned page No. book No. _ County Official

corner this sheet

U.S. FOREST SERVICE

Cross Index No. _