## INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
   Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated. corners.
- Description of monument and accessories set to perpetuate the corner position.
   Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.


  6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED COR	NER	RECO	RDAT	ION
---------------	-----	------	------	-----

cs 1/16 of s33 36 N., 26 W., \_\_ P.M.M. County

- No previous record.
- II. No evidence found.

III.At the calculated position, set a 3/4 in. diam., 30 ins. long, alum. rod 24 ins. in the ground with alum. cap



A pine, 39 ins. diam., bears East, 45.5 ft. dist., mkd. CS 1/16 S33 BT.

No other available bearing trees.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, West, 3 ft. Magnetic Declination: 20 East



1 39" PINE

	(	CERTIFICATION	
Kevin	Α.	Todd	

certify the information shown he

Signature Ground Party C

Ronald A. Pearson

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101-et seq., M.C.A.)


10/1/92 Reg. No. \_ 9008 LS

Employer: U.S. FOREST SERVICE

## **SKETCH OF CORNER**

Lincoln Office of Clerk and Recorder, County of \_ \_ . This "corner record" was filed for record on \_\_\_\_\_ was noted on the cross-index plat and is assigned page No. oral M. Commings book No. \_ County Official i.

36 N 26 W



corner this sheet