

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, not discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Center 1/4 Sec. 20 T. 36N R. 27W P.M.M. Lincoln County

RECORD: The center 1/4 of Section 20 was set per Section Subdivision and Certificate of Survey No. 2256 by LS 7238.

FOUND: Found a 5/8" rebar with plastic cap stamped "7328S". As a part of our survey we tied the West 1/4 and South 1/4 to the Center 1/4. The position for the Center 1/4 was within positional tolerance relative to the West 1/4 and South 1/4.

PERPETUATION: At the exact position of the 5/8" rebar/cap I set a 2 1/2"x30" aluminum monument with 3/4" aluminum cap marked as shown on the reverse side from which:

An 8" Larch bears N12°E, 26.10 feet, marked "C 1/4 S20 BT"
A 20" Doug Fir bears N70°E, 48.20 feet, marked "C 1/4 S20 BT"

The rebar/cap was placed inside the aluminum monument.
Bearing tree tags were placed on the bearing trees facing the monument and Land Monument signs were placed on the back.
The blazes were painted red.

SEE REVERSE SIDE FOR DIAGRAM

SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on March 3, 1999 was noted on the cross-index plat and is assigned page No. 10315 book No. _____

Coral M. Cummings
County Official

Cross Index No. P7 T. 36N R. 27W PMM

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

CERTIFICATION

I, Craig Binnall
certify the information shown herein is true and correct.


Craig Binnall
Signature of Ground Party Chief

I, James R. Staples
certify that this corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)


James R. Staples
Signature of Surveyor & Seal

Date: 7-20-98 Reg. No. 9958

Employer: J.R.S. Surveying, Inc.



Sec. 20



*- corner this sheet

