

INSTRUCTIONS

1. Original and/or subse record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

• CERTIFIED CORNER RECORDATION

Corner $\frac{1}{4}$ corner between Sec. 9 & 10 T. 36N R. 87W P.M.M. Lincoln County

Record

Set a post 3' long 3" sq. 24" in the ground from which
 a pine 14" diam. bears N. 13°W 151 lks
 a pine 40" diam. bears S. 60°30'E 120 lks.

Found rebar set by Doyle '25165'

See C. of S. No. 669 for adjacent corners.

CERTIFICATION

I, _____
 certify the information shown herein is true and correct.

Signature Ground Party Chief

I, D. K. Marquardt

certify that this Corner Record correctly represents work performed
 by me or under my direction in compliance with the "Corner
 Recordation Act" (70-22-101, et seq., M.D.A.)

D. K. Marquardt
 Signature of Surveyor & Seal

Date: 7-2-81 Reg. No. 2289ES

Employer: _____


SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner
 record" was filed for record on the 17th July day of 1981
 was noted on the cross-index plat and is assigned page No. 1109, in
 book No. 1

Thomas L. Vaughan, Jr.
 County Official

Cross Index No. G-13 T. 36N R. 87W P.M.M.

Sec. 9



• - corner this sheet