CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record: Lava Stone
Willow 5 inch S. 75 1/2° E. 10 lks.
Fir 4 inchess N 25 1/4° W 39 lks.

assigned page No. 12/4, in book No.

FORM 125 - 41605

Found BLM brass caps

15 pine (200 cz 340 w. T36N RZBW)
(5 1/5 c)
(5 1/5 c)
(5 23 | 524

Cross Index No. R-21 T. 36N R. 28W Mer.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

	Date of work:
SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE	

Surveyor's Seal	. D. K. Marguandt	DIAGRAM OF CORNER:
Surveyor's Seal	certify that the information shown herein is true and correct.	N. T36N_R28W ¼
•	Signature of Ground Party Chief	j
	I, D. K. Marquardt	23 🗘 24
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	Corner recorded on the sheet
	Signature of Suveyor	
	£ S 2989 Registration Number	
Office of Clerk and Recorder, Count	ty of Lineals	
This "corner record" was filed for	record on the 12th day of August 1981, was	s noted on the cross-index plat and is