## CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record: Stone


Pine 12 inches North 29 1/4° East 212 lks.

Pine 12 inches South 71° East 186 lks.

Pine 12 inches South 87° West 368 lks.

Pine 12 inches North 52° 45' West 234 lks.

Found BLM brass caps



DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work:....

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's	Seal
------------	------

I, D. K. Marquardt certify that the information shown herein is true and correct.

Signature of Ground Party Chief

Danged Signature of Surveyor

DIAGRAM OF CORNER:

14 13 23 24

Corner recorded on the sheet

ES 2388 Registration Number

Office of Clerk and Recorder, County of Sinceln

This "corner record" was filed for record on the 2 day of Organit 1981, was noted on the cross-index plat and is assigned page No. 1215, in book No.

Eleaner of Clerk and Recorder, County of Sinceln

County Official County Official County Official ROBER Mer.