FIED LAND CORNER RECORD MPM, LINCOLN DUNTY, MONTANA DESCRIPTION OF COLLNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) ORIGINAL 1813 GLO NOTES VOL 2842 -PAGE 83 POST 3" X 3" X 3' SET 24" IN GROUND, MKD CORNER DESC: ON W. FACE 114.5 WITNESS MARKS: 9" FIR BEARS N 18° 30'W, 141 LKS, MKD 1/45 BT 10" FIR BEARS N 9°E, 114 LKS, MKD /4 S BT FOUND: POST FOR CORNER WAS NOT RELOVERED TWO BT WERE RELOVERED, BUT THEY ARE PINE THE INSTEAD OF DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Date of work: 18 OCT 1966 IRON PIPE WITH BRONZE CAP INTERSECTION OF THE BRONZE CAP STAMPED T3UN R27W COFE 1966 SCRIBED 14" PINE BEARS N 33° 20'W, 111/2 LKS MKD SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.) RECOVERED PECOVERED 9" PINE 10" PINE MKD 1/4 587 MKD 1/25BT SET 14" PINE MKD FS/RM 87 DIAGRAM OF CORNER: I LAVERNE Surveyor's Seal certify that the information shown herein is true and correct STO BRONZE CAP Signature of Ground Party Chief STAMPED T36N R27N LAWRENKE A. SIGNANI certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. = Corner recorded on the sheet TONAL LAND Saurence U. Signature of Surveyor 11422 Registration Number Office of Clerk and Recorder, County of \_\_\_\_\_\_ 12:22 KM This "corner record" was filed for record on the 2/ day of . 19.62., was noted on the cross-index plat and is assigned page No. 15 k in book No. 1 Buck County Official FORM 125-41605 Cross Index No. G - 5 T 36 \_\_\_\_ R\_ZZ\_\_\_\_ Mer.