CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Not Previously Set

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: Nov. 1975

Set USFS Brass Cap at the proper location for W 1/16 $\frac{S}{S} = \frac{24}{5}$, from which:

A Fir 14" diam. bears S54°W 33.12*

A Fir 14" diam. bears South 27.06'

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey No. 181.

Surveyor's Seal	S. R. Smith	DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.	N. 736N
	3 R Smil	S 24
	Signature of Ground Party Chief	S 25
	i, Dean K. Marquardt	
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this	' R 27W
	recordation form and approve the same.	•
	Signature of Surveyor	— = Corner recorded on the sheet
	ES2989 Registration Number	
Const. Charles and Dance has Con-	L	
	unty of Ainealn	
his "corner record" was filed f	or record on the 38 day of Truckly 1976, wa	s noted on the cross-index plat and is
signed page No. 401		Mac Walson Depuly

Cross Index No.....