CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Original Record: Post 3' long x 3" square from which

Spruce 12" bears N. 70W. 251ks.

Spruce 10" bears 5.37°E. 251ks

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Set brass cape 5.750c by single proportion 9.85.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See Certificate of Survey # 152

Surveyor's Seal	ι, S. R. Smith	DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.	N. T36NRZTW
	S. R. Smil	ſ
	Signature of Ground Party Chief	4 24
	i, D. K. Marquardt	_
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	
	DX Magnarde	= Corner recorded on the sheet
	Signature of Surveyor	
	E.S. 2989 Registration Number	
Office of Clerk and Recorder, C	County of Linealin	
This "corner record" was filed f	for record on the 28th day of Anguary 1976, was	noted on the cross-index plat and is
assigned page No. 420	for record on the 28th day of Anguary 1976, was also in book No.	the Mac Water Dyrata
•	0.75	

Form 125—41328

Gross Index No. 2.23 T. 360 R. 2700 Mer.